

RESOLUTION A.277 (VIII) adopted on 20 November 1973
RECOMMENDATION ON PERFORMANCE STANDARDS FOR RADAR REFLECTORS

INTER-GOVERNMENTAL MARITIME
CONSULTATIVE ORGANIZATION



ASSEMBLY - 8th session
Agenda item 10

Distr.
GENERAL

A VIII/Res.277
14 December 1973

Original: ENGLISH

IMCO

RESOLUTION A.277(VIII)
adopted on 20 November 1973

RECOMMENDATION ON PERFORMANCE STANDARDS FOR
RADAR REFLECTORS

THE ASSEMBLY,

NOTING Article 16(i) of the Convention on the Inter-Governmental Maritime Consultative Organization concerning the functions of the Assembly,

RECOGNIZING that small vessels will improve the range and probability of their radar detection, if fitted with radar reflectors,

HAVING CONSIDERED the Report of the Maritime Safety Committee on its twenty-fifth session,

RESOLVES

- (a) to adopt the Recommendation on Performance Standards for Radar Reflectors, set out at Annex hereto,
- (b) to recommend that Member Governments should require all vessels of less than 100 tons gross tonnage operating in international waters and adjacent coastal areas to be fitted, if practicable, with a radar reflector complying with performance standards not inferior to those shown in the Annex to this Resolution.

A VIII/Res.277

- 2 -

ANNEX

RECOMMENDATION ON
PERFORMANCE STANDARDS FOR RADAR REFLECTORS

1. Introduction

- (a) Small craft referred to in paragraph 2 of this Recommendation should be fitted with radar reflectors to improve the range and probability of their radar detection.
- (b) Radar reflectors should comply with the minimum performance requirements as specified in this Recommendation.
- (c) In the following paragraphs the echoing areas specified are those for the frequency of 9.3 GHz (corresponding to a wave-length of 3.2 cm).

2. Application

- (a) All vessels of less than 100 tons gross tonnage operating in international waters and adjacent coastal areas should, if practicable, be fitted with a radar reflector.
- (b) The radar reflector should be of an approved type with an adequate polar diagram in azimuth, and an echoing area:
 - (i) preferably, of at least 10 m^2 , mounted at a minimum height of 4 m above water level; or
 - (ii) if this is not practicable, of at least 40 m^2 , mounted at a minimum height of 2 m above water level.

3. Performance

- (a) Reflectors should be capable of performance around 360° in azimuth using a typical marine navigational radar.
- (b) The echoing areas referred to in paragraph 2 correspond to the maximum values of the main lobes of the polar diagram.

- (c) The azimuthal polar diagram should be such that the response over a total angle of 240° is not less than -6dB with reference to the maxima of the main lobes and that the response should not remain below -6dB over any single angle of more than 10° .

4. Construction

The reflector should be capable of maintaining its reflection performance under the conditions of sea states, vibration, humidity and change of temperature likely to be experienced in the marine environment.

5. Installation

- (a) Fixing arrangements should be provided so that the reflector can be fitted either on a rigid mount or suspended in the rigging.
 - (b) If there is a preferred orientation of mounting (generally the top point only), this should be clearly marked on the reflector.
-

RESOLUTION A.277 (VIII) adopted on 20 November 1973
RECOMMENDATION ON PERFORMANCE STANDARDS FOR RADAR REFLECTORS